

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 December 2000 (07.12.2000)

PCT

(10) International Publication Number
WO 00/73221 A1

(51) International Patent Classification⁷: C02F 11/18, 1/02

(21) International Application Number: PCT/NO00/00176

(22) International Filing Date: 26 May 2000 (26.05.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
19992612 31 May 1999 (31.05.1999) NO

(71) Applicant (for all designated States except US): CAMBI
AS [NO/NO]; Billingstadsletta 83, N-1396 Billingstad
(NO).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SOLHEIM, Odd, Egil
[NO/NO]; N-1395 Hvalstad (NO).

(74) Agent: PROTECTOR INTELLECTUAL PROPERTY
CONSULTANTS AS; P.O. Box 5074 Majorstua, N-0301
Oslo (NO).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE,
DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU,
ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS,
LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO,
NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR,
TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: A METHOD OF AND ARRANGEMENT FOR CONTINUOUS HYDROLYSIS OF ORGANIC MATERIAL



(57) Abstract: A method of and arrangement for continuous hydrolysis of organic material in the form of sludge with a dry solids content of 1-20% are described. The method includes the following steps: (a) heating a sludge containing the organic material with a low content of abrasive components and a dry solids content of 1-20%, to a temperature of approximately 100 °C; (b) mixing the sludge with steam at a pressure of 1-4 bar a; (c) leading the sludge/steam mixture to a preheating tank (4); (d) increasing the pressure of the sludge/steam mixture from 3 to 10 bar a; (e) leading the sludge/steam mixture to a reactor (7); (f) depressurising the sludge/steam mixture to 1-4 bar a in a depressurising tank (10); (g) separating sludge and steam, and possibly (h) cooling the sludge further. The arrangement includes: (i) a feed pump connected to a first heat exchanger (2) for heating the incoming sludge through heat exchange with the outgoing sludge; (ii) a mixing device (3) for mixing the sludge with steam, connected to the first heat exchanger (2); (iii) a preheating tank (4) connected to the mixing device (3); (iv) a pump (5) for increasing the pressure of the steam/sludge mixture by from 3 to 10 bar a, connected to the preheating tank (4); (v) a reactor (7) at a temperature of 130-180 °C, connected to the pump (5); (vi) a depressurising tank (10) connected to the reactor (7), which depressurising tank (10) includes a nozzle (9) for depressurising the steam/sludge mixture to 1-4 bar a.

WO 00/73221 A1